

### CXP Variants

CXP Speed	Bit Rate	Assembly Max Length
CXP-3	3.125 Gbit/s	30 Meter
CXP-6	6.25 Gbit/s	30 Meter
CXP-12	12.5 Gbit/s	20 Meter

Above chart represent typical practical cable length. Anything beyond will be classified as "Fit for used". Stable operation in some applications cannot be guaranteed.

UNIT : mm  
UNLESS OTHERWISE SPECIFIED  
ASSY LENGTH TOLERANCE

< 150mm = ±10  
≥ 150mm and < 250mm = ±15  
≥ 250mm and < 500mm = ±20  
≥ 500mm and < 1000mm = ±30  
≥ 1000mm and < 5000mm = ±50  
5000mm and above = ±100


This document is the property of Alysium-Tech. It must not be copied or otherwise disclosed without prior written consent

**RoHS COMPLIANT**

### BILL OF MATERIALS

Item	Description
1	DIN1.0/2.3 Male Moulded (OD4.04) <BLK>
2	A36-2065, 12GHz UHD Video Coaxial Cable 75ohm 23AWG PVC [OD=4.04mm] <BLK>
3	Cable Label
4	Heat Sealed PE Bag
5	Label On Bag (ALY CE)

### WIRING DIAGRAM



### PACKAGING DETAIL

